IBF-Graphix Posfast

PRODUCT FEATURES

HIGH PERFORMANCE POSITIVE PLATE FOR UV CTP DEVICES

UP TO 150.000* UNBAKED

ELECTROCHEMICALLY GRAINED AND ANODIZED

FAST EXPOSURE

EXCELLENT CONTRAST AFTER PROCESSING

OUTSTANDING DEVELOPER LATITUDE

HIGH RESISTANCE TO ABRASION, SCRATCHING AND FINGERPRINTS

FAST ROLL UP LEADING TO PAPER AND **INK SAVINGS**

LOW WATER CONSUMPTION **ON PRESS**

www.ibf.com.br

POSITIVE UV PLATE FOR CTCP AND CONTACT FRAMES



IBF-Graphix

Posfast

SPECIFICATION

► HIGH PERFORMANCE POSITIVE PLATE FOR UV CTP DEVICES

Plate Type	Positive working plate, for UV CTCP and analog workflows
Coating	Blue
Image Color (Exposed)	Blue (Visible color change after exposure)
Spectral Sensitivity	360 - 405nm
Gauge	0.14mm, 0.20mm, 0.30mm and 0.40mm
Lighting Conditions	24 hours yellow safe light
Substrate	Electrochemically grained and anodized
Energy	45-55 mJ/cm²
Resolution	1% to 99% at 250 LPI
Operating Conditions	40% to 70% RH; 18C to 26C (65F to 78F)
Storage Conditions	30% to 70% RH; 10C to 30C (50F to 86F)
Run Length	Up to 150.000 impressions unbaked* Up to 1.000.000 impressions baked*
Processor	Standard positive plate processor

Auxiliary Products

Developer	IBF PD21 Developer
Gum	IBF Eco Finisher
Baking Solution IBF SH	IBF SH
Plate Cleaner	IBF Eco Cleaner
Storage Gum	IBF 14 Bè Gum
Image Remover	IBF Positive Remover



www.ibf.com.br

IBF - INDÚSTRIA BRASILEIRA DE FILMES S/A
Headquartes: Rua Lauro Müller, 116 - 10th floor
Botafogo - Rio de Janeiro
ZIP: 22290-906 Phone: +55 21 2103-1000
Manufacturing: Rua Dr. Sabino Arias, 187
Mantiqueira - Xerém, Duque de Caxias / RJ
ZIP: 25250-613 Phone: +55 21 2103-7500
CNPJ: 33255787/0001-91 - Indústria Brasileira
www.ibf.com.br

^{*} Depending on press conditions, paper and ink. Consult IBF plate specialist.